

GelBit™

The **colored bit** that corresponds to its grit!



Orange: Rapid Grind



Green: Standard Grind



Yellow: Fine Grind



Blue: Extra Fine Grind

GelBit™ PRODUCT IDENTIFICATION

Item Number	Description
GB 3.4 R	Gel Bit™ ¾" Rapid
GB 3.4 S	Gel Bit™ ¾" Standard
GB 3.4 F	Gel Bit™ ¾" Fine
GB 3.4 EF	Gel Bit™ ¾" Extra Fine
GB 1.0 R	Gel Bit™ 1" Rapid
GB 1.0 S	Gel Bit™ 1" Standard
GB 1.0 F	Gel Bit™ 1" Fine
GB 1.0 EF	Gel Bit™ 1" Extra Fine



TECHNIGLASS

80 Thompson Street
N. Tonawanda, NY 14120 USA
Tel. 716.564.8888
Fax 716.564.8889
Email info@techniglass.net
www.techniglass.net

Made in USA • U.S. & Foreign Patents Pending

GelBit™

The **colored bit** that corresponds to its grit!

TECHNIGLASS

An affordable and attractive bit designed with the same performance as traditional grinding bits.

The Gel Bit™ features a high-quality diamond grit available in 1" (25.4mm) and 3/4" (19.05mm) diameters with Extra Fine, Fine, Standard, and Rapid Grind varieties.

Identifiable and Attractive

Bright Neon Color corresponds to grit for easy identification.

Affordable Quality

Gel Bits™ offer the same quality as traditional grinding bits, yet at a fraction of the cost!

Reduces Chipping

Polymeric holder absorbs shock and reduces chipping.

Does Not Freeze Up on Shaft

Gel Bits™ are designed to disengage from the shaft easily and quickly.

Universal

Like all other Techniglass products, Gel Bits™ accommodate every type of grinder.



The GelBit™ Advantage

Gel Bit™

Each type of Gel Bit™ has its own color, which corresponds to its grit. This allows for easy identification when you need to change the bit in a hurry.



Traditional Bits

It can be very confusing to select a bit when they all look exactly alike. Why take chances? You can be assured you are using the correct grit with Gel Bit™.



How to Install

Open Bit-Holder

Loosen the screw on the Gel Bit™ by using an Allen key to turn it counter-clockwise.

Add Grinding Bit

Slide the bit down onto the motor shaft until approximately 1/8" of the diamond surface is above the workplace.

Lock

Tighten the screw on the flat area of the motor shaft using the Allen key and turning clockwise.